

# ClariSure PA Polypropylene Mini Cartridge Filter

**mdi** ClariSure PA mini cartridge filters are 100% polypropylene, very high retention efficiency pleated cartridge filters offering large filtration area.

These filters have heat stable construction and are used as prefilters to sterilizing membrane cartridge filters.

## **Special Features**

- Very high retention efficiency (99.99%)
- Heat stable construction
- No media migrating
- Wide chemical compatibility
- Biologically inert
- Each filter comes with an individual certificate of quality
- Total tracebility:
   Unique identification number is laser etched on each filter

Complies with USDFA 21 CFR 210.3(b)(6)

Meets and Exceeds USDFA 21 CFR 177.1520



## **Applications**

- Pre-filtration of fermentor air
- Pre-filtration of small volume parenterals


## **Specifications**

Construction				
Pore size	0.5µm, 1µm, 1.2µm, 2.5µm, 5µm, 8µm, 10µm			
Filter Media	Polypropylene			
Support Layers	Polypro	ppylene		
Body and Core	Polypro	Polypropylene		
Size				
Size	2.5"	5″		
Effective Filtration Area (Nominal)	1000cm²	2000cm²		
Operational				
Max. Operating Temperature	80 °C @ < 30 psi (2 Kg/cm²)			
Max. Differential Pressure	50 psi (3.5 Kg/cm²) @ 25 °C			
Sterilization	Autoclavable/In-line steam sterilizable at 121 °C for 30 minutes, 100 cycles			
Assurance				
Toxicity	Passes Biological reactivity test, In Vivo, as per USP <88> for Class VI plastics			
Non Fiber Releasing	Passes test as per USP and comply with USFDA 21 CFR Part 210.3(b)(6) for fiber release			
Extractables with WFI	Passes NVR test as per USP <661>			
Oxidizable Substances	Passes test as per USP <1231>	Passes test as per USP <1231>		
Particle Shedding	The filtrate complies with USP <788> test for particulate matter in injections			
Indirect Food Additive	All Polypropylene components meet the FDA Indirect Food Additive requirements cited in 21 CFR 177.1520			
Good Manufacturing Practice	These products are manufactured in a facility which adhe	eres to Good Manufacturing Practices.		
Quality Management System	ISO-9001Certified			
USFDA	DMF No. 015554			


DST CPPAXMX1549C

#### **Water Flow Rates**

#### 2.5" ClariSure PA Cartridge Filters



#### 5" ClariSure PA Cartridge Filters



## **Ordering Information**

Туре		
	Code	
ClariSure PA	СРРА	

Size			
Length and filtration Area	Code		
2.5"	50		
5″	53		

Pore Size		
Code		
04		ľ
05		ŀ
10		Ļ
06		
07		ŀ
17		ŀ
08		ŀ
	04 05 10 06 07 17	Code  04  05  10  06  07  17

Adap	tor	
	Code	
4463	E0	
4463B	H0	
4440	U0	
Seal-K	G0*	
Seal-O	F0**	
Seal-M	JO	

Elastomer			
	Code		Г
Silicone	SS		١

Sterility		
	Code	
Non Sterile	1	

Pack Size		
	Code	
1	01	

\*GO adapter code is not available with any elastomer. Please mention XX in place of elastomer code while ordering \*\*Adapter code FO is available only in 5" cartridge filters

#### Example

				i	1	
СРРА	50	04	U0	SS	1	01

## **Advanced Microdevices Pvt. Ltd.**

20-21, Industrial Area, Ambala Cantt-133 006, INDIA

Tel:+91-171-2699290, 2699471 E-mail:info@mdimembrane.com Website:www.mdimembrane.com

DST CPPAXMX1549C