

Nylon-66 Membrane Disc Filter Type HNN

Nylon-66 Membrane Disc Filter Type HNN

mdi Nylon membrane disc filters are made of Nylon-66 resin. These are hydrophilic, non-media migrating, biologically inert absolute membrane filters useful for aqueous as well as organic solvent filtration. These are HPLC certified to ensure accuracy and reliability of the results besides preventing instrument downtime.

The HNN membranes are produced in validated processes to ensure high inter and intra-lot consistency.

Special Features

- Minimal extractables
- Absolute retention
- High heat resistance
- Wide chemical compatibility
- Absolute reliability
- · Biologically inert
- Hydrophilic


Application

 HPLC sample preparation and solvent filtration

Integrity Test Data (Bubble Point, Water Wetted)

Pore Size	Bubble Point (Water)
0.2 µm	≥ 50 psi (3.52 Kg/cm²)
0.45 µm	≥ 32 psi (2.25 Kg/cm²)

Water Flow Rate



Specification

Material of Construction

Nylon-66 polymer

Pore Size

 $0.2~\mu m$, $0.45~\mu m$

Diameter

13 mm, 25mm, and 47 mm, 90mm, 142mm

Thickness

150 ± 20 µm

Wettability

Hydrophilic

Bacterial Retention

0.2μm: LRV> 7 for B. diminuta as

per cm² of filter area

0.45µm: LRV > 7 for S. marcescens

per cm² of filter area

Maximum Operating Temperature

≤ 80 °C continuous

Sterilization

Autoclavable at 121°C for 30 minutes

Biosafety

Passes the biological tests for Class VI of plastics as described in USP

Fiber Release

Passes test as per USP and comply with USFDA 21 CFR Part 210.3(b)(6) for fiber release

Particle Release:

The filtrate complies with USP <788> test for particulate matter in injectables

Oxidizable Matter

Passes test as per USP

Extractables with Water

Within limits as specified in USP



Ordering Information

Туре		Size		Pore Size		XX	XX	Sterility		Pack Size	
	Code	Dia	Code		Code				Code	Qty	Code
HNN	HNNX	13 mm	03	0.2 µm	01			Non Sterile	1	100	04
		25 mm	06	0.45 µm	02						
		47 mm	09								
		90 mm	14								
		142 mm	16								
Example											
HN	INX 09)	01		XX	XX	1		04	