



## Rapid Test Components Sample Pad

Product Glassfiber Sample Pad for Rapid Test

Intended Use Development/Manufacture of Lateral Flow Immunoassay Test Kit

**Product Variant** Type GFB-R\* (GFB-R4, GFB-R7L)

**Composition** Proprietary fibrous material

Physical Properties

Property	GFB-R* (0.35)	GFB-R* (0.6)
Appearance	White	White
Tare weight (mg/cm²)	5.5 <u>+</u> 1.5	9 <u>+</u> 3
Thickness	370 <u>±</u> 70μm	610 <u>+</u> 120 µm

Performance Characteristics

Product	Mean Wicking Time (Seconds) 4cm Distance with Distilled Water			
Туре	GFB-R4	GFB-R7L		
GFB-R*(0.35)	50 <u>+</u> 20			
GFB-R*(0.6)	50 <u>+</u> 20	55 <u>+</u> 20		

Supply Format Strip/sheet of desired dimension

**Storage** Store and handle in accordance with all current regulations and standards.

**Condition** Store in original foil packing at 1 - 35 °C. Avoid direct sunlight.

Caution: Material should be kept away from heat radiators.

**Shelf Life** Two Year from the date of dispatch, stored under above conditions.

Ordering Information						
Product	Description					
Туре	Thickness (mm)	Strip/Sheet Length	Strip/Sheet Width	Quantity (Nos.)		
GFB-R4	0.35	As per requirement	As per requirement	As per requirement		
GFB-R7L	0.6					

## Example:

GFB-R4	0.35	300 mm	20 mm	Nos.

DSTGFBR1034E