

AseptiPrime® KS

Taking Throughput to the next level

Sterile filtration with upto 3x smaller filter area

AseptiPrime® KS is designed to fulfil the above need. These low protein binding filters, incorporate a very high porosity optimized pre-filter PES membrane with unique pore structure that ensures high loading capacity for suspended contaminants and high volume handling. This results in much higher throughput when compared with other available sterilizing filters.

The robust, highly retentive final membrane layer ensures that *AseptiPrime® KS* filters meet international regulatory requirements for microbial retention and deliver sterile filtrate.

AseptiPrime® KS capsule filters offer additional advantages of linear scalability of filter area for smooth transitions from lab scale to pilot to process scale and widest range of end connections for quick and reliable connectivity to the existing fittings.

Bio-pharmaceutical manufacturing is a complex, multistep process which involves a very wide variety of process streams under different process conditions at different steps. These process streams include cell culture media, media additives, growth regulators in the upstream and post centrifuge cell harvest supernatants, post viral inactivation intermediates, buffers, and high value product concentrates in the downstream. Filtration and purification of such a wide spectrum of fluid streams, to achieve varied objectives at each step, is quite a challenge for the process owner.

Microfiltration accounts for a very high (approximately 25%) of the filtration and purification costs. Sterilizing filters are a huge component of this cost as these are critical for multiple applications across the entire biopharmaceutical process. Some of these are:

- Sterile filtration of culture media and product concentrates
- Protection of expensive virus filters and chromatography columns
- Control of microbial load throughout the process chain

There is therefore a continuous need to enhance the throughput obtained from 0.2µm/0.1µm filters with various process streams.



mdi
Membrane Technologies

AseptiPrime® KS

High Throughput Sterilizing Filters

AseptiPrime® KS capsule filters use **mdi** PES membrane in Polypropylene housing. No adhesives or glue are used in the manufacturing process and all bonding is done by heat welding.

The products are deeply validated for use in Biopharmaceutical applications. AseptiPrime® KS are manufactured in class 10,000 clean rooms and ISO 9001 certified facilities. Packaging is done in double polybags for convenience of taking AseptiPrime® KS in clean areas for making disposable assemblies for subsequent sterilization.

Applications

Sterile Filtration of

- Cell culture media
- Cell culture media containing serum
- Media additives
- pH adjusters
- Final product concentrates

Bioburden Reduction/ Particulate Removal

- Buffers
- Centrifuge supernatants
- Clarified cell lysates

Key Features

- Very high throughput
- Absolute retention
- 100% integrity tested
- Low protein binding
- Very low hold up volume in filters
- High flow rates
- Bioburden maintained below 1000 cfu/device
- Endotoxin level certified to be <0.25 EU/ml
- Widest range of end connections
- Products available for total scalability from a few ml to thousands of liters
- Total traceability through unique serial number for each filter
- Individual certificate of quality for each device
- Sterilizable by Autoclaving or Ethylene Oxide

Validation Services

The regulatory requirements emphasize on the need to validate the efficacy of the 'Sterilizing Filter' with drug product under simulated worst-case conditions of use.

mdi provides validation services supported by customized validation protocols and world class test facilities to assist you in filter validations with your specific drug product.


Performance Data

High Throughputs


mdi AseptiPrime® KS filter consistently outperformed other available sterilizing filters by exhibiting much higher throughput with a wide variety of fluid streams.

The large throughput difference allows use of filters with much smaller filter area and enhance process economy.


Also, optimized filter sizes do away with the possibilities of mid batch change out of filters or having to isolate a complete batch because it could not be processed.




Soy Media




RPMI




Yeast Peptone Dextrose



Luria Bertani



6M Urea



6M Guanidine HCl

Quality Assurance

mdi quality management system emphasizes on quality by design rather than by end product testing. Robust processes are developed for product manufacturing and are continuously monitored to ensure that the products meet their predetermined specifications and lot to lot reproducibility is ensured.

Certificate of Quality

Each capsule filter is accompanied by individual certificate of quality to ensure traceable documentation at user's end.

It certifies the product compliance to various regulatory as well as user requirements.

Validated for Microbial Retention

Integrity test data have been correlated to actual microbial retention with *Acholeplasma laidlawii* (ATCC 23206) and with *B.diminuta* (ATCC 19146) as per ASTM F838-05 to establish acceptable integrity test values.

Samples from each lot are subjected to microbial challenge test before final lot release.

100% Integrity Tested

Each *AseptiPrime*® KS is tested for integrity to comply with validated Acceptable Integrity Test Specifications.

Flow Rate

Each lot is tested for clean water flow rates to ensure that flow rates are within the specifications.

Protein Adsorption

AseptiPrime® KS filters are validated for low protein binding to ensure minimal active ingredient losses when used for filtration of high value proteins.

0.2 µm <i>AseptiPrime</i> ® Filters	Protein Binding (0.75% BSA)
25 mm, 5 cm ²	1.45 µg
50 mm, 20 cm ²	6.3 µg
1", 250 cm ²	80.5 µg
2", 500 cm ²	175 µg
10", 6000 cm ²	1925 µg

Pressure, Temperature Endurance

AseptiPrime® KS filters are validated to endure high operating pressure and temperature conditions which may be encountered during use.

These filters are also validated for high burst pressure to ensure user safety in case of inadvertent pressure build-up.

Extractables

Extractables/leachables from sterilizing filters, used at various stages of a biopharmaceutical manufacturing process, will add on and may impact the impurity profile of the desired product.

AseptiPrime® KS filters are validated to exhibit low extractables under harsh extraction conditions.

Bioburden Testing

Device bioburden is tested as per ISO 11737-1 and assured to be <1000 cfu/device.

Endotoxin Testing

Aqueous extracts exhibit < 0.25 EU/ml as established by Limulus Amebocyte Lysate (LAL) Test as per USP <85>

Total Traceability

AseptiPrime® KS filters come with completely traceable lot numbers and unique identification number to facilitate easy and fast retrieval of manufacturing and quality control data associated with each filter.

These unique lot and identification numbers are laser etched on each filter device and also printed on the labels of the box in which individual filter is packed.

Packaging Integrity

AseptiPrime® KS filters are fitted with vent caps and are packed in bags to ensure package integrity during transit as well as to prevent particulate contamination while transferring to clean room assembly or process areas.

Other Regulatory Compliance

- **Complies with USFDA 21 CFR 210.3(b)(6) for fiber release**
- **Complies with USFDA 21 CFR 177.1520 for indirect food additives**
- **Materials of construction tested for toxicity as per Biological Reactivity Tests, In-vivo, USP <88> for class VI Plastics**
- **Complete filter devices tested for cytotoxicity as per Biological Reactivity Tests, In-vitro, USP <87>**

Linear Upscaling from R&D to Production Process

Scientists are concerned about filter fluid interaction impacting the stability, purity, strength etc. of the drug product, and they take a keen interest in filter selection at the formulation development stage itself. Although preliminary compatibility data support initial filter selection, for stability studies detailed filter validations are required to provide enough documented evidence to justify specific filter use.

A critical requirement that needs to be addressed at this stage is of scalability from R&D to pilot scale to full scale production processes.

mdi offers a wide range of *AseptiPrime*® KS filters to provide linear scale up from lab scale to production process. While scaling up the process, the appropriate size filter can be selected by increasing the effective filtration area of filter proportionate to the process fluid volumes.

All Materials of construction as well as manufacturing process are identical for all filter devices starting from 5 cm² to 18000cm² hence process scaling can be facilitated without triggering additional validation studies for given process conditions. **mdi** provides complete documentation for each of the *AseptiPrime*® KS filters there by reducing the additional validation cost and time.



AseptiPrime® KS
25mm, 5cm²



AseptiPrime® KS
50mm, 20cm²



AseptiPrime® KS
1", 250cm²



AseptiPrime® KS
2", 500cm²



AseptiPrime® KS
5", 1000cm²



AseptiPrime® KS
8", 2000cm²



AseptiPrime® KS
10", 6000cm²



AseptiPrime® KS
20", 12000cm²



AseptiPrime® KS
30", 18000cm²

Filter Devices	EFA* (Nominal)	Hold up Volume
<i>AseptiPrime</i> ® KS 25 mm	5cm ²	< 50µl
<i>AseptiPrime</i> ® KS 50 mm	20cm ²	< 200µl
<i>AseptiPrime</i> ® KS 1"	250cm ²	< 5ml
<i>AseptiPrime</i> ® KS 2"	500cm ²	< 25ml
<i>AseptiPrime</i> ® KS 5"	1000cm ²	< 45ml
<i>AseptiPrime</i> ® KS 8"	2000cm ²	< 60ml
<i>AseptiPrime</i> ® KS 10"	6000cm ²	–
<i>AseptiPrime</i> ® KS 20"	12000cm ²	–
<i>AseptiPrime</i> ® KS 30"	18000cm ²	–

Easy Connect

Widest Range of End Connections

Biopharmaceutical processes involve transfer of high value fluids through multiple process steps. Making high quality, reliable, flexible and functionally convenient connectivity with filters is of utmost value to the bio-processors.

mdi AseptiPrime® KS filters offer a wide range of reliable end connections for functional convenience and customized connectivity.

Validated for Performance

These end connections are manufactured with tight dimensional tolerance and are validated for strength and connection integrity under extreme use conditions as well as for their ability to withstand prevalent sterilization methods including EO sterilization and autoclaving.



3/4" Sanitary Flange



1 1/2" Sanitary Flange



1/2" Hose Barb



1/2" Single Stepped Hose Barb



1/4" Stepped Hose Barb



Quick Connector

Some end connections available with AseptiPrime® KS

Customized Connectivity

mdi AseptiPrime® KS filters are available in a wide range of end connections and are also customized to offer different inlet-outlet combinations to meet the unique connectivity needs in biopharmaceutical process assemblies where, for example, stainless steel components with sanitary flange connections are sometimes required to be connected to single use disposable systems through quick-connectors or hose barb connections.



**1 1/2" Sanitary Flange
to 1/2" Barb Hose**



**1 1/2" Sanitary Flange
to 3/4" Sanitary Flange**



**AseptiPrime® with HighSecurity
1/2" hose barb connection**

Specifications

Construction

Membrane	0.1µm/0.2 µm Hydrophilic PES
Pre-filter Membrane	0.1µm: 0.3µm or 0.5µm PES 0.2µm: 0.5µm PES
Support Layers	Polyester
Plastic Parts	Polypropylene

Integrity Testing / Retention

Bubble Point	0.1µm: ≥ 26 psi (1.82 Kg/cm ²) with 50% IPA ≥ 65 psi (4.56 Kg/cm ²) with Water 0.2µm: ≥ 50 psi (3.52 Kg/cm ²) with Water
Max. Air Diffusion Flows per 10" Capsule Filter	0.1µm: ≤ 29 ml/min @ 50 psi (3.52 Kg/cm ²) with water 0.2µm: ≤ 30 ml/min @ 37 psi (2.6 Kg/cm ²) with water
Microbial Retention	for 0.1µm: LRV >7 for <i>Acholeplasma laidlawii</i> (ATCC 23206) per cm ² for 0.2µm: LRV >7 for <i>Brevundimonas diminuta</i> (ATCC 19146) per cm ²

Operational

Sterilization	By Irradiation	Autoclavable at 125°C for 30 minutes, 3 cycles and it cannot be in-line steam sterilized			
	By Gas	Sterilizable by Ethylene Oxide			
Shelf Life		3 years after EO Sterilization			
		25 mm	50 mm	1", 2", 5", 8"	5", 10", 20", 30"
Max. Operating Temperature		55 °C	60 °C	80 °C @ < 30 psi (2 Kg/cm²)	
Max. Differential Pressure		75 psi (5 Kg/cm²) @ 25 °C	42 psi (3 Kg/cm²) @ 30 °C	60 psi (4 Kg/cm²) @ 30 °C	

Assurance

Toxicity	Passes Bioreactivity test, In Vivo, as per USP <88> for Class VI plastics
Cytotoxicity	Passes Biological Reactivity Tests, In vitro, USP <87> for Cytotoxicity
Bacterial Endotoxin	Aqueous extracts exhibit < 0.25 EU/ml as established by Limulus Amebocyte Lysate (LAL) Test as per USP <85>
Non Fiber Releasing	Passes test as per USP and comply with USFDA 21 CFR Part 210.3(b)(6) for fiber release
TOC and Conductivity	Meets the WFI requirements of USP for TOC <643> and Conductivity <645> after a 5 liter flush for 5" capsule filters and 10 liter for 10" capsule filters
pH Compatibility	Compatible with pH range of 1-10
Extractables with WFI	Passes NVR test as per USP <661>
Indirect Food Additives	Comply with USFDA 21 CFR Part 177.1520
Oxidizable Substances	Passes test as per USP <1231>
Quality Management System	ISO-9001 Certified
USFDA	DMF No. 015554

Dimensions

Disc Capsule Filters

Size	25mm	50mm
Effective Filtration Area (cm²)	5	20
End Connections	End to End Length	
1/4" SHB I/O	-	79 mm
3/4" Sanitary Flange I/O	-	51 mm
Female Luer Lock Inlet/ Male Luer Slip Outlet	23 mm	-
1/8" Hose Barb I/O	36 mm	-

Operational Radius	15 mm	28 mm
--------------------	-------	-------

Small Capsule Filters

Size	1"	2"	5"	8"
Effective Filtration Area (cm²)	250	500	1000	2000
End Connections	End to End Length			
1/4" SHB I/O	94 mm	122 mm	172 mm	223 mm
3/4" Sanitary Flange Inlet I/O	85 mm	104 mm	155 mm	206 mm
1 1/2" Sanitary Flange I/O	92 mm	112 mm	165 mm	216 mm
1/2" Hose Barb I/O	90 mm	112 mm	162 mm	214 mm
1/2" Single Step Hose Barb I/O	-	115 mm	165 mm	218 mm
1 1/2" Sanitary Flange Inlet 1/2" Hose Barb Outlet	-	112 mm	165 mm	216 mm

Operational Radius	40 mm	65 mm	65 mm	65 mm
--------------------	-------	-------	-------	-------

Large Capsule Filters


Size	5"	10"	20"	30"
Effective Filtration Area (cm²)	3000	6000	12000	18000
End Connections	End to End Length			
1 1/2" Sanitary Flange I/O	205 mm	326 mm	605 mm	865 mm
1/2" Single Step Hose Barb I/O	218 mm	332 mm	628 mm	888 mm
1 1/2" Sanitary Flange Inlet 1/2" Hose Barb Outlet	212 mm	332 mm	618 mm	878 mm
3/8" Hose Barb I/O	211 mm	332 mm	634 mm	885 mm
3/4" Sanitary Flange I/O	214 mm	335 mm	x	x

Operational Radius	78 mm	78 mm	78 mm	78 mm
--------------------	-------	-------	-------	-------

Typical Water Flow Rates


0.1µm AseptiPrime® KS

25mm and 50mm capsule filter




0.2µm AseptiPrime® KS

25mm and 50mm capsule filter




0.1µm AseptiPrime® KS

1", 2", 5" and 8" Capsule Filters




0.2µm AseptiPrime® KS

1", 2", 5" and 8" Capsule Filters




0.1µm AseptiPrime® KS

5", 10", 20" and 30" Capsule Filters



0.2µm AseptiPrime® KS

5", 10", 20" and 30" Capsule Filters



End Connection Type:

E: 1½" Sanitary Flange

B: ¼" Stepped Hose Barb (for 50mm only)

MN: End Connections: Female Luer Lock Inlet/Male Luer Slip Outlet

Ordering Information

AseptiPrime® KS 25mm PES Membrane Inline Capsule filters

Type		Size		Pore Size		Inlet/Outlet		X	X	Sterility		Pack Size	
	Code		Code		Code		Code				Code		Code
AseptiPrime® KS (0.3µm optimized pre-filter)	IKX9	25mm	06	0.1µm	36	Female Luer Lock	M			Non Sterile	1	100	04
AseptiPrime® KS (0.5µm optimized pre-filter)	IKX7			0.2µm*	01	Male Luer Slip	N			EO Sterile	2		
						1/8" Hose Barb	H						
						1/4" Hose Barb	B						
Example:													
IKX7		06		01		MN		X	X	1		04	

Example for Non Sterile: IKX70601MNXX104

Example for EO Sterile: IKX70601MNXX204

*0.2µm capsule filters are available with 0.5µm pre-filter only

AseptiPrime® KS 50mm PES Membrane Inline Capsule filters

Type		Size		Pore Size		Inlet/Outlet		X	X	Sterility		Pack Size	
	Code		Code		Code		Code				Code		Code
AseptiPrime® KS (0.3µm optimized pre-filter)	VKX9	50mm	10	0.1µm	36	1/4" SHB	B			Non Sterile	1	10	02
AseptiPrime® KS (0.5µm optimized pre-filter)	VKX7			0.2µm*	01	3/4" Sanitary Flange	S			EO Sterile	2		
						Female Luer Lock	M						
Example:													
VKX7		10		01		BB		X	X	1		02	

Example for Non Sterile: VKX71001BBXX102

Example for EO Sterile: VKX71001BBXX202

*0.2µm capsule filters are available with 0.5µm pre-filter only

Note: Inlet/Outlet Connections and Pack Sizes available with different diameter filters as follows:

Connections Available		
Inlet/Outlet	25mm	50mm
1/4" - 3/4" Stepped Hose Barb	X	√
3/4" Sanitary Flange	X	√
Female Luer Lock	Inlet Only	√
Male Luer Slip	Outlet Only	X
1/8" Hose Barb	√	X
Male Luer Lock	Outlet Only	X
1/4" Hose Barb	√	X

Pack Size Available		
Pack Size	25mm	50mm
10/Pack	X	√
100/Pack	√	X

Ordering Information

AseptiPrime® KS PES Membrane Small Capsule filters

Type		Size		Pore Size		Inlet/Outlet		X	X	Sterility		Pack Size			
	Code		Code		Code		Code				Code		Code		
AseptiPrime® KS (0.3µm optimized pre-filter)	DKX9	1"	51	0.1µm	36	¼" SHB	A			Non Sterile	1	1	01		
		2"	52	0.2µm*	01	¼" MNPT (18 TPI)	B			EO Sterile	2				
		5"	53			¼" BSP (19 TPI)	M								
AseptiPrime® KS (0.5µm optimized pre-filter)	DKX7	8"	57			¼" BSP (19 TPI) with O-ring	P								
						¼" BSP	F								
						½" MNPT	C								
						½" Hose Barb	D								
						1½" Sanitary Flange	E								
						¾" Sanitary Flange	S								
						Quick Connector	J								
						½" Single Step Hose Barb	Q								
						Female Luer Lock	U								
						Male Luer Slip	W								
						¾" Hose Barb	N								
						¾" Hose Barb	I								
						¼" Single Step Hose Barb	R								
Example:		DKX7	57	01	DD			X	X		1	01			

Example for Non Sterile: DKX75101QXX101

Example for EO Sterile: DKX75101QXX201

* 0.2µm capsule filters are available with 0.5µm pre-filter only

Note: Inlet/Outlet Connections available with different Sizes/Length as follows:

Inlet/Outlet	Size/Length			
	1"	2"	5"	8"
¼" Stepped Hose Barb	√	√	√	√
½" Single Step Hose Barb	X	√	√	√
¼" Single Step Hose Barb	√	√	√	√
½" Hose Barb	√	√	√	√
1½" Sanitary Flange	√	√	√	√
¾" Sanitary Flange	√	√	√	√
Quick Connector	√	√	√	√
½" MNPT	X	√	√	√
¼" MNPT (18TPI)	√	√	√	√
¼" BSP (19 TPI)	Inlet Only	X	X	X
¼" BSP (19 TPI) with O-ring	Inlet Only	X	X	X
¼" BSP	Inlet Only	√	√	√
Female Luer Lock	√	√	√	√
Male Luer Slip	Outlet Only	X	X	X
¾" Hose Barb	√	√	Outlet Only	X
¾" Hose Barb	√	√	√	√

Ordering Information

AseptiPrime® KS PES Membrane Large Capsule filters

Type		Size		Pore Size		Inlet/Outlet		X	Inline/ T-Line	Sterility		Pack Size			
	Code		Code		Code		Code		Code		Code		Code		
AseptiPrime® KS (0.3µm optimized pre-filter)	LKX9	5"	53	0.1µm	36	½" Single Step Hose Barb	Q	X	Inline	X	Non Sterile	1	1	01	
		10"	54	0.2µm*	01	1½" Sanitary Flange	E								
		20"	55			¾" Sanitary Flange	S								
AseptiPrime® KS (0.5µm optimized pre-filter)	LKX7	30"	56			¾" Hose Barb	I		T-Line	T	EO Sterile	2			
						1" Hose Barb	Z								
Example:															
LKX7		54		01		EE		X	T	1		01			

Example for Non Sterile: LKX75301QXX101

Example for EO Sterile: LKX75301QXX201

* 0.2µm capsule filters are available with 0.5µm pre-filter only

Note: Inlet/Outlet Connections available with different Sizes/Length as follows:

Inlet/Outlet	Inline				T-Line		
	5"	10"	20"	30"	10"	20"	30"
½" Single Step Hose Barb	√	√	√	√	X	X	X
1½" Sanitary Flange	√	√	√	√	√	√	√
¾" Sanitary Flange	√	√	X	X	X	X	X
¾" Hose Barb	√	√	√	√	X	X	X
1" Hose Barb	X	√	√	√	X	X	X

ADVANCED MICRODEVICES PVT. LTD.

20-21, Industrial Area, Ambala Cantt- 133 006, India

Tel: +91 - 171-2699290, 2699471

E-mail: info@mdimembrane.com

Website: www.mdimembrane.com