



Data Sheet

AseptiSure® TF

Hydrophobic PTFE Membrane Cartridge Filters

Pharmaceutical and Biopharmaceutical manufacturing involves sterile filtration of air/gases for a multitude of critical processes such as air sparging, bioreactor venting, fermentor exhaust, dry powder filling, WFI tank venting etc.

The critical nature of these processes and associated high costs require the highest degree of reliability for the filter device with regard to its retention efficiency, flow rates, service life and mechanical and thermal stability.

mdi PTFE Membrane Cartridge filters are hydrophobic *AseptiSure® TF* filters offering absolute retention. These filters are designed for sterilizing filtration of gases as well as aggressive solvents and liquids.

The high quality of membrane and design of cartridge assures long life and ability to withstand adverse process conditions experienced during use.

These are also validated for other key performance parameters such as chemical compatibility, extractable, heat stability, flow rates, blow through and ability to withstand accidental reverse pressure. These are available in a variety of pore sizes to suit specific microfiltration needs in critical and specialized process applications for air as well as liquid.

AseptiSure® TF

PTFE Membrane Cartridge Filters

Datasheet

mdi AseptiSure® TF PTFE membrane cartridge filters are deeply validated for use in pharmaceutical and Biopharmaceutical applications. These filters are manufactured in class 10,000 clean rooms and ISO 9001 certified facilities

Key Features

- Absolute retention
- Heat sealed
- No leaching
- High heat Stability
- Wide chemical compatibility
- Biologically inert
- Long service life
- Non-toxic material of construction
- Pre-flushed to minimize particulate release after installation
- 100% integrity tested
- High flow rates
- Bioburden maintained below 1000 cfu/device
- Endotoxin level certified to be <0.25 EU/ml
- Unique identification number is laser etched on each filter
- Individual certificate of quality for each device
- Sterilizable by Autoclaving/Steaming in place (SIP)

Applications

- Fermentors venting and aeration
- Sterile filtration of API and injectables
- Sterile compressed air for pharma machineries
- Sterile air for dry powder injectables filling

Validation Services

The regulatory requirements emphasize on the need to validate the efficacy of the filter with drug product under simulated worst-case conditions of use.

mdi provides validation services supported by customized validation protocols and world class test facilities to assist you in filter validations with your specific drug product.

mdi quality management system emphasizes on quality by design rather than by end product testing. Robust processes are developed for product manufacturing and are continuously monitored to ensure that the products meet their predetermined specifications and lot to lot reproducibility is ensured.

Certificate of Quality

Each cartridge filter is accompanied by individual certificate of quality to ensure traceable documentation at user's end. It certifies the product compliance to various regulatory as well as user requirements.

Validated for Microbial Retention

Integrity test data have been correlated to actual microbial retention to establish acceptable integrity test values. Samples from each lot are subjected to microbial challenge test before final lot release.

100% Integrity Tested

Each *AseptiSure*® TF is tested for integrity to comply with validated Acceptable Integrity Test Specifications.

Flow Rate

Each lot is tested for clean water flow rates to ensure that flow rates are within the specifications.

Pressure, Temperature Endurance

AseptiSure® TF filters are validated to endure high operating pressure and temperature conditions which may be encountered during use.

Extractables

Extractables/leachables from *AseptiSure*® TF filters, used at various stages of a biopharmaceutical manufacturing process, will add on and may impact the impurity profile of the desired product.

AseptiSure® TF filters are validated to exhibit low extractables under harsh extraction conditions.

Bioburden Testing

AseptiSure® TF bioburden is tested as per ISO 11737-1 and assured to be <1000 cfu/device.

Total Traceability

AseptiSure® TF filters come with completely traceable lot numbers and unique identification number to facilitate easy and fast retrieval of manufacturing and quality control data associated with each filter.

These unique lot and identification numbers are laser etched on each filter device and also printed on the labels of the box in which individual filter is packed.

Packaging Integrity

AseptiSure® TF filters are packed in bags to ensure package integrity during transit as well as to prevent particulate contamination while transferring to clean room process areas.


Other Regulatory Compliance

- Complies with USFDA 21 CFR 210.3(b)(6) for fiber release
- Complies with USFDA 21 CFR 177.1520 for fractional dissolution
- Materials of construction tested for toxicity as per Biological Reactivity Tests, In-vivo, USP <88> for class VI Plastics

Adapters and Dimensions


2.5" Mini Cartridge Filters

4463 Adapter (E0)




Total Length : 75 mm
Diameter : 56 mm

Seal-K Adapter (G0)




Total Length : 132 mm
Diameter : 56 mm

Seal-K Adapter (G0)




Total Length : 77 mm
Diameter : 56 mm

4440 Adapter (U0)




Total Length : 118 mm
Diameter : 56 mm

4463B Adapter (H0)



Total Length : 69 mm
Diameter : 56 mm


Seal-O Adapter (F0)



Total Length : 117 mm
Diameter : 56 mm


5" Mini Cartridge Filters

4463 Adapter (E0)



Total Length : 128 mm
Diameter : 56 mm

4463B Adapter (H0)




Total Length : 123 mm
Diameter : 56 mm

Adapters and Dimensions


Standard Cartridge Filters

10" Cartridge Filter- 7P Adapter with Fin (A0)




Total Length : 315 mm
Diameter : 70 mm

30" Cartridge Filter- 7P Adapter with Fin (A0)



Total Length : 795 mm
Diameter : 70 mm

20" Cartridge Filter- 7P Adapter with Fin (A0)



Total Length : 555 mm
Diameter : 70 mm

Adapter and Elastomers Availability Chart

Mini Cartridge Filters		
Adapters	2.5"	5"
4463	√	√
4463B	√	√
4440	√	√
Seal-K	√	√
Seal-O	X	√
Seal-M	√	√

Mini Cartridge Filters	
Adapters	Elastomer
	Silicone
4463	√
4463B	√
4440	√
Seal-K	X
Seal-O	√
Seal-M	√

Standard Cartridge Filters				
Adapters	5"	10"	20"	30"
7P	√	√	√	√
7P without Fin	√	√	√	√
28 with Fin	X	√	√	√
'O'	X	√	√	√

Standard Cartridge Filters				
Adapters	Elastomers			
	Silicone	Viton	EPDM	FEP Encapsulated Viton
7P	√	√	√	√
7P without Fin	√	√	√	√
28 with Fin	√	√	√	X
'O'	√	√	√	X

Linear Upscaling from Pilot Scale to Production Process

Datasheet

Scientists are concerned about filter fluid interaction impacting the stability, purity, strength etc. of the drug product, and they take a keen interest in filter selection at the formulation development stage itself. Although preliminary compatibility data support initial filter selection, for stability studies detailed filter validations are required to provide enough documented evidence to justify specific filter use.

A critical requirement that needs to be addressed at this stage is of scalability from pilot scale to full scale production processes.

mdi offers a wide range of *AseptiSure*® TF filters to provide linear scale up from lab scale to production process. While scaling up the process, the appropriate size filter can be selected by increasing the effective filtration area of filter proportionate to the process fluid volumes.

All Materials of construction as well as manufacturing process are identical for all filter devices starting from 1000 cm² to 18000 cm² hence process scaling can be facilitated without triggering additional validation studies for given process conditions. **mdi** provides complete documentation for each of the *AseptiSure*® TF filters there by reducing the additional validation cost and time.



***AseptiSure*® TF, 2.5"**
EFA: 1000 cm²



***AseptiSure*® TF, 5"**
EFA: 2000 cm²



***AseptiSure*® TF, 5" Large**
EFA: 3000 cm²



***AseptiSure*® TF, 10"**
EFA: 6000 cm²



***AseptiSure*® TF, 20"**
EFA: 12000 cm²



***AseptiSure*® TF, 30"**
EFA: 18000 cm²

*EFA: Effective Filtration Area

Specifications

Mini Cartridge Filters

Datasheet

Construction

Membrane	Hydrophobic PTFE
Support Layers	Polypropylene
Plastic Parts	Polypropylene
O rings	Silicone

Integrity Testing / Retention

Pore Size	0.2µm	0.45µm	
Bubble Point	22psi (1.52 Bar) with 70% IPA/Water Solution	10psi (0.69 Bar) with 70% IPA/Water Solution	
Microbial Retention	LRV >7 for <i>Brevundimonas diminuta</i> (ATCC 19146) per cm ²	LRV >7 for <i>Serratia marcescens</i> (ATCC 14756) per cm ²	
Water Intrusion Test	2.5"	< 0.3 ml/min @ 2.0kg/cm ²	—
	5"	< 0.6 ml/min @ 2.0kg/cm ²	—

Size

Size	2.5"	5"
Effective Filtration Area (Nominal)	1000cm ²	2000cm ²

Operational

Max. Operating Temperature	95 °C @ < 2 Kg/cm ² (30 psi)
Max. Differential Pressure	50 psi (3.5 Kg/cm ²) @ 25 °C
Reverse Pressure	< 0.7 Kg/cm ² (10 psi) @ 25 °C
Sterilization	Autoclavable/In-line steam sterilizable at 121 °C for 30minutes, 100 cycles @ Δp=5 psi (0.3kg/cm ²)

Assurance

Toxicity	Passes Biological Reactivity tests, In Vivo, as per USP <88> for Class VI plastics
Bacterial Endotoxin	Aqueous extracts exhibit < 0.25 EU/ml as established by Limulus Amebocyte Lysate (LAL) Test as per USP <85>
Bioburden	Bioburden level is < 1000 cfu/filter device as per ISO 11737-1
Particle Shedding	The filtrate complies with USP <788> test for particulate matter in injections
Non Fiber Releasing	Passes test as per USP and comply with USFDA 21 CFR Part 210.3(b)(6) for fiber release
Extractables with WFI	Passes NVR test as per USP <661>
Indirect Food Additives	All Polypropylene components meet the FDA Indirect Food Additive requirements cited in 21 CFR 177.1520
Oxidizable Substances	Passes test as per USP <1231>
Quality Management System	ISO-9001 Certified
USFDA	DMF No. 015554

Specifications

Standard Cartridge Filters

Datasheet

Construction

Membrane	Hydrophobic PTFE
Support Layers	Polypropylene
Plastic Parts	Polypropylene
O rings	Silicone
	Viton
	EPDM
	FEP Encapsulated Viton

Integrity Testing / Retention

Pore Size	0.2µm	0.45µm
Air Diffusion Flow	≤ 45ml/min @ 16 psi (1.12Kg/cm ²)	≤ 45ml/min @ 8 psi (0.56Kg/cm ²)
Microbial Retention	LRV >7 for <i>Brevundimonas diminuta</i> (ATCC 19146) per cm ²	LRV >7 for <i>Serratia marcescens</i> (ATCC 14756) per cm ²

Size

Size	5"	10"	20"	30"
Effective Filtration Area (Nominal)	3000cm ²	6000cm ²	12000cm ²	18000cm ²

Operational


Max. Operating Temperature	95 °C @ < 2 Kg/cm ² (30 psi)
Max. Differential Pressure	50 psi (3.5 Kg/cm ²) @ 25 °C
Reverse Pressure	< 0.7 Kg/cm ² (10 psi) @ 25 °C
Sterilization	Autoclavable/In-line steam sterilizable at 121 °C for 30minutes, 100 cycles @ Δp=5 psi (0.3kg/cm ²)

Assurance


Toxicity	Passes Biological Reactivity tests, In Vivo, as per USP <88> for Class VI plastics
Bacterial Endotoxin	Aqueous extracts exhibit < 0.25 EU/ml as established by Limulus Amebocyte Lysate (LAL) Test as per USP <85>
Bioburden	Bioburden level is < 1000 cfu/filter device as per ISO 11737-1
Particle Shedding	The filtrate complies with USP <788> test for particulate matter in injections
Non Fiber Releasing	Passes test as per USP and comply with USFDA 21 CFR Part 210.3(b)(6) for fiber release
Extractables with WFI	Passes NVR test as per USP <661>
Indirect Food Additives	All Polypropylene components meet the FDA Indirect Food Additive requirements cited in 21 CFR 177.1520
Oxidizable Substances	Passes test as per USP <1231>
Quality Management System	ISO-9001 Certified
USFDA	DMF No. 015554

Typical Air Flow Rates Mini Cartridge Filters

0.2µm AseptiSure® TF, 2.5" Mini Cartridge Filters




0.2µm AseptiSure® TF, 5" Mini Cartridge Filters




Typical Air Flow Rates Standard Cartridge Filters


0.2µm AseptiSure® TF, 5" Standard Cartridge Filters




0.2µm AseptiSure® TF, 10" Standard Cartridge Filters



0.2µm AseptiSure® TF, 20" Standard Cartridge Filters



0.2µm AseptiSure® TF, 30" Standard Cartridge Filters



AseptiSure® TF PTFE Membrane Mini Cartridge Filter

Type		Size		Pore Size		Adapter		Elastomer		Sterility		Pack Size	
	Code		Code		Code		Code		Code		Code		Code
AseptiSure® TF	CPTF	2.5"	50	0.2µm	01	4463	E0	Silicone	SS	Non Sterile	1	1	01
		5"	53	0.45µm	02	4463B	H0						
						4440	U0						
						Seal-K	G0*						
						Seal-O	F0**						
						Seal-M	J0						

Example:

CPTF	50	01	E0	SS	1	01
------	----	----	----	----	---	----

*G0 adapter code is not available with any elastomer. Please mention XX in place of elastomer code while ordering

**Adapter code F0 is available only in 5" cartridge filters.

AseptiSure® TF PTFE Membrane Standard Cartridge Filter

Type		Size		Pore Size		Adapter		Elastomer		Sterility		Pack Size	
	Code		Code		Code		Code		Code		Code		Code
AseptiSure® TF	CPTF	5"	53	0.2µm	01	7P	A0	Silicone	SS	Non Sterile	1	1	01
		10"	54	0.45µm	02	7P without fin	A1	EPDM	SE				
		20"	55			28 with fin	C0	Viton	SV				
		30"	56			'O'	D0	FEP Encapsulated Viton	FV**				

Example:

CPTF	54	01	A1	SS	1	01
------	----	----	----	----	---	----

*Size 5" is available in Adapter Code A0 (7P) and A1 (7P without fin) only

**FV is available in adapter code A0 (7P) and A1 (7P without fin) only

Advanced Microdevices Pvt. Ltd.

20-21, Industrial Area, Ambala Cantt-133 006, INDIA

Tel : +91-171-2699290, 2699471

E-mail : info@mdimembrane.com

Website : www.mdimembrane.com